

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method of facilitating redirection of traffic between a server and a client to between the client and a nearest replica selected from a plurality of replicas, the method comprising:

receiving a packet that is ~~travelling~~ traveling between a client and a server or between the client and a replica;

42 when the received packet is a start packet that is ~~travelling~~ traveling from the client to the server, altering the start packet to indicate that the start packet should be forwarded to any replica that duplicates the data content of the server;

when the received packet is an acknowledgement packet that is received first in response to the forwarded start packet, altering the acknowledgement so that it spoofs the server when the acknowledgement originates from the replica;

when the received packet is an acknowledgement that is not received first in response to the forwarded start packet, sending a reset to the replica or the server identified as a source of the received packet; and

when the received packet is a subsequent packet received after the start packet and the acknowledgement packet, altering the subsequent packet so that it spoofs the server when the subsequent packet originates from the replica or altering the subsequent packet so that it goes to the replica when the subsequent packet originates from the client.

2. (Original) A method as recited in claim 1, wherein the server is spoofed by replacing a source identifier of the received packet with a destination identifier of the start packet.

3. (Original) A method as recited in claim 1, wherein the server is spoofed by encapsulating the received packet with a source identifier that equals a destination identifier of the start packet.

4. (Original) A method as recited in claim 1, wherein the received packet is encapsulated and the server is spoofed by cracking the received packet.

5. (Original) A method as recited in claim 1, further comprising:

42
determining that the acknowledgement packet originates from the replica when a source identifier of the acknowledgement packet does not equal a destination identifier of the start packet;

determining that the subsequent packet originates from the replica when the source identifier of the subsequent packet does not equal the destination identifier of the start packet; and

determining that the subsequent packet is going to the server when the destination identifier of the subsequent packet equals the destination identifier of the start packet.

6. (Original) A method as recited in claim 1, wherein the start packet is altered by adding a tag to or modifying the tag of the start packet to indicate that the start packet should be forwarded to any replica that duplicates data content of the server.

7. (Original) A method as recited in claim 1, wherein the start packet is only altered when the start packet is associated with web data.

8. (Original) A method as recited in claim 7, wherein the start packet is associated with web data when the start packet has a destination port utilized for accessing web data.

9. (Original) A method as recited in claim 1, further comprising:

storing a destination identifier of the start packet; and

storing and associating a source identifier of the acknowledgement packet
with the stored destination identifier of the start packet.

10. (Original) A method as recited in claim 9, wherein the destination identifier
of the start packet and source identifier of the acknowledgement packet are stored and associated
as an entry within a table.

A2
11. (Original) A method as recited in claim 9, wherein the source identifier of the
acknowledgement packet is only stored and associated with the destination identifier of the start
packet when the source identifier of the acknowledgement packet does not indicate the server.

12. (Original) A method as recited in claim 11, further comprising deleting the
destination identifier of the start packet when the source identifier of the first acknowledgement
packet does not indicate the server.

13. (Original) A method as recited in claim 9, further comprising:

prior to storing and associating the source identifier of the
acknowledgement packet, cracking the acknowledgement packet to obtain the
source identifier when the acknowledgement packet has been encapsulated, and

wherein the server is spoofed for the acknowledgement by cracking the
acknowledgement packet.

[
14-19. (cancelled)

14
20. (currently amended) A computer system operable to facilitate redirection of
traffic between a server and a client to between the client and a nearest replica selected from a
plurality of replicas, the computer system comprising:

a memory; and

a processor coupled to the memory,

wherein at least one of the memory and the processor are adapted to provide:

receiving a packet that is travelling between a client and a server or between the client and a replica;

when the received packet is a start packet that is travelling from the client to the server, altering the start packet to indicate that the start packet should be forwarded to any replica that duplicates the data content of the server;

when the received packet is an acknowledgement packet that is received first in response to the forwarded start packet, altering the acknowledgement so that it spoofs the server when the acknowledgement originates from the replica;

when the received packet is an acknowledgement that is not received first in response to the forwarded start packet, sending a reset to the replica or the server identified as a source of the received packet; and

when the received packet is a subsequent packet received after the start packet and the acknowledgement packet, altering the subsequent packet so that it spoofs the server when the subsequent packet originates from the replica or altering the subsequent packet so that it goes to the replica when the subsequent packet originates from the client.

¹⁵
~~21~~. (Original)

A computer system as recited in claim ¹⁴~~20~~ wherein the server is spoofed by replacing a source identifier of the received packet with a destination identifier of the start packet.

¹⁶
~~22~~. (Original)

A computer system as recited in claim ¹⁴~~20~~, wherein the server is spoofed by encapsulating the received packet with a source identifier that equals a destination identifier of the start packet.

¹⁷
~~23~~. (Original)

A computer system as recited in claim ¹⁴~~20~~, wherein the received packet is encapsulated and the server is spoofed by cracking the received packet.

¹⁸
~~24.~~ (Original)

A computer system as recited in claim ¹⁴~~20~~, the at least one of the memory and the processor are further adapted to provide:

determining that the acknowledgement packet originates from the replica when a source identifier of the acknowledgement packet does not equal a destination identifier of the start packet;

determining that the subsequent packet originates from the replica when the source identifier of the subsequent packet does not equal the destination identifier of the start packet; and

^{A2}
determining that the subsequent packet is going to the server when the destination identifier of the subsequent packet equals the destination identifier of the start packet.

¹⁹
~~25.~~ (Original)

A computer system as recited in claim ¹⁴~~20~~, wherein the start packet is altered by adding a tag to or modifying the tag of the start packet to indicate that the start packet should be forwarded to any replica that duplicates data content of the server.

²⁰
~~26.~~ (Original)

A computer system as recited in claim ¹⁴~~20~~, wherein the start packet is only altered when the start packet is associated with web data.

²¹
~~27.~~ (Original)

A computer system as recited in claim ²⁰~~26~~, wherein the start packet is associated with web data when the start packet has a destination port utilized for accessing web data.

²²
~~28.~~ (Original)

A computer system as recited in claim ¹⁴~~20~~, the at least one of the memory and the processor are further adapted to provide:

storing a destination identifier of the start packet; and

storing and associating a source identifier of the acknowledgement packet with the stored destination identifier of the start packet.

²³
~~29.~~ (Original)

A computer system as recited in claim ²²~~28~~, wherein the destination identifier of the start packet and source identifier of the acknowledgement packet are stored and associated as an entry within a table.

²⁴
~~30.~~ (Original)

A computer system as recited in claim ²²~~28~~, wherein the source identifier of the acknowledgement packet is only stored and associated with the destination identifier of the start packet when the source identifier of the acknowledgement packet does not indicate the server.

²⁵
~~31.~~ (Original)

A computer system as recited in claim ²⁴~~30~~, the at least one of the memory and the processor are further adapted to provide deleting the destination identifier of the start packet when the source identifier of the first acknowledgement packet does not indicate the server.

²⁶
~~32.~~ (Original)

A computer system as recited in claim ²²~~28~~, the at least one of the memory and the processor are further adapted to provide:

prior to storing and associating the source identifier of the acknowledgement packet, cracking the acknowledgement packet to obtain the source identifier when the acknowledgement packet has been encapsulated, and

wherein the server is spoofed for the acknowledgement by cracking the acknowledgement packet.

33-38. (cancelled)

²⁷
~~39.~~ (currently amended)

A computer program product for facilitating redirection of traffic between a server and a client to between the client and a selected one from a plurality of replicas, the computer program product comprising:

at least one computer readable medium;

computer program instructions stored within the at least one computer readable product configured to cause a processing device to:

receive a packet that is ~~travelling~~ traveling between a client and a server or between the client and a replica;

when the received packet is a start packet that is ~~travelling~~ traveling from the client to the server, alter the start packet to indicate that the start packet should be forwarded to any replica that duplicates the data content of the server;

when the received packet is an acknowledgement packet that is received first in response to the forwarded start packet, altering the acknowledgement so that it spoofs the server when the acknowledgement originates from the replica;

when the received packet is an acknowledgement that is not received first in response to the forwarded start packet, sending a reset to the replica or the server identified as a source of the received packet; and

when the received packet is a subsequent packet received after the start packet and the acknowledgement packet, alter the subsequent packet so that it spoofs the server when the subsequent packet originates from the replica, or alter the subsequent packet so that it goes to the replica when the subsequent packet originates from the client.

40-44. (cancelled)

28
45.

(currently amended) An apparatus for facilitating redirection of traffic between a server and a client to between the client and a nearest replica selected from a plurality of replicas, the apparatus comprising:

means for receiving a packet that is ~~travelling~~ traveling between a client and a server or between the client and a replica;

means for altering the start packet to indicate that the start packet should be forwarded to any replica that duplicates the data content of the server when the

received packet is a start packet that is ~~travelling~~ traveling from the client to the server;

means for altering the acknowledgement so that it spoofs the server when the acknowledgement originates from the replica when the received packet is an acknowledgement packet that is received first in response to the forwarded start packet;

means for sending a reset to the replica or the server identified as a source of the received packet when the received packet is an acknowledgement that is not received first in response to the forwarded start packet; and

A2
means for altering the subsequent packet so that it spoofs the server when the received packet is a subsequent packet received after the start packet and the acknowledgement packet and when the subsequent packet originates from the replica or altering the subsequent packet so that it goes to the replica when the subsequent packet originates from the client.

[
46-47. (cancelled)
